

SEALTEK

Advanced Coating Technologies

4 Victoria Street, Van Reyneveld, Strand
063 827 0580 / 079 073 7894
sales@sealtekcape.co.za



WEATHERCOAT

Highly abrasion-resistant (>10,000 cycles)

For interior or exterior wall use



Product Overview: An eco-friendly, acrylic decorative wall paint. WeatherCoat is a water-based, adhesion-promoted, UV-stable, and highly durable paint—making it an ideal decorative coating for both interior and exterior walls.

Surface Preparation	<ul style="list-style-type: none">➤ Ensure the substrate has been thoroughly cleaned and is free of dust, debris, or any substances that may affect adhesion.➤ Confirm that the substrate is completely dry before applying the product.
Method of Application	<ul style="list-style-type: none">➤ WeatherCoat is pre-packaged in 5L & 20L bucket. Open the bucket and mix thoroughly at medium speed before application.➤ Ensure the substrate has been properly prepared as outlined above.➤ Cover all surrounding and non-sprayable areas with masking tape to prevent damage or overspray. <p>Airless Spray Application – Apply the first coat using an airless sprayer. Once the coat is touch dry, a flash coat may be applied if needed.</p> <p>Roll-On Application – Roll on the first coat of paint. Once the first coat is touch dry, apply the second coat. A third flash coat may be applied if necessary.</p> <p>Brush-On Application – Brush on the first coat. Once the first coat is touch dry, apply the second coat. A third coat may be applied if needed.</p>
Practical Coverage	70 m ² per 20-litre bucket with a 2–3 coat application
Cleaning	Our paint is water-based; therefore, paint and application tools can be cleaned with running water.
Drying Time	<ul style="list-style-type: none">➤ Touch Dry or recoating – 1-2 Hours at ± 25 °C➤ Fully Cured - 7 Days at ± 25°C
Colours	Standard colours for waterproofing are Grey, White, Black, Terra Cotta, and Green. However, we can supply waterproofing in any of our 90 standard colours, and select colours can be matched upon request.